

In the Claims:

Please add the claims as follows:

- 5 1. (Original) The arrangement (1) for detection of unauthorized removal of electronic equipment (2) that is connected to a power source (3),
the arrangement (1) is arranged between the power source (3) and the electronic equipment (2) and has a first current
10 recognizing element (10) that senses current that is delivered to the electronic equipment (2) characterized therein that the arrangement is arranged to send a signal (12) to the electronic equipment (2) wherein the signal is adapted to bounce back to the arrangement (1) so that detection of
15 unauthorized removal is obtained when a current sensed by the first current recognizing element (10) is lower than a certain predetermined level and that the bouncing back of the signal (12) is not indicated.
- 20 2. (Original) The arrangement according to patent claim 1 characterized therein that the arrangement (1) further has an alarm unit (11) that is arranged to send an alarm signal to an alarm center when a detection of unauthorized removal has been detected.
- 25 3. (Original) The arrangement according to patent claim 1 characterized therein that the arrangement (1) further has a second current recognizing element (13) that senses the current delivered from the power source (3), the arrangement
30 (1) is arranged to send the signal (12) to the electronic equipment (2) when the current sensed by the current recognizing element (13) is lower than a predetermined level.
- 35 4. The arrangement according to any of the patent claims 1 or 2 characterized therein that the arrangement (1) further has a unit (14) that includes batteries wherein the unit (14) sends

the signal (12) to the electronic equipment (2).

5. (Currently amended) The arrangement according to patent claim 1 ~~any of the patent claims 1, 2, or 3~~ characterized
5 therein that the arrangement (1) further has a unit (15) that
is connected to an audio-contact of the electronic equipment,
the unit (15) is arranged to sense a resistance that has a
predetermined value, the unit (15) is arranged to send a
signal to the alarm center (11) if the resistance sensed is
10 different from this value.
6. (Original) A method for detecting unauthorized removal of
electronic equipment (2) that is connected to a power source
(3),
15 wherein a current delivered to the electronic equipment (2) is
sensed by a first current recognizing unit (10) that is
included in an arrangement (1), the arrangement (1) is
arranged between the power source (3) and the electronic
equipment (2), characterized therein that a signal (12) is sent
20 to the electronic equipment (2), the signal is adapted to
bounce back to the arrangement (1) so that a detection of
unauthorized removal is obtained when a current sensed by the
first current recognizing element (10) is lower than a
predetermined value and the bouncing back of the signal (12)
25 is not indicated.
7. (Original) The method according to patent claim 6,
characterized therein that an alarm signal is sent from an
alarm unit (11), that is included in the arrangement (1), to
30 an alarm center when a detection of unauthorized removal is
obtained.

8. (Currently amended) The method according to patent claim 6
~~any of patent claims 6 or 7~~ characterized therein that a
current delivered from the power source (3) is sensed by a
second current recognizing element (13) that is included in
5 the arrangement (1) so that the signal (12) is sent from the
arrangement (1) to the electronic equipment (2) when a current
sensed by the second current recognizing element (13) is lower
than a certain predetermined level.
- 10 9. (Currently amended) The method according to any of the
patent claim 6 ~~patent claims 6, 7 or 8~~ characterized therein
that the signal (12) is sent from a unit (14) that is included
in the arrangement (1).
- 15 10. (Currently amended) The method according to patent claim
7 ~~any of the patent claims 7-9~~ characterized therein that the
unit (15), included in the arrangement (1), is connected to an
audio-contact of the electronic equipment (2) so that a
resistance that has a predetermined value is sensed by the
20 unit (15) so that a signal is sent from the unit (15) to the
alarm unit (11) when the resistance is different from this
value.